

Powerline Wifi TP-Link



NETWORKING WIRELESS TP-LINK Modello:1 TL-WPA4220 + 1 TL-PA4010 Velocità:600 Mbps Compatibilità:Homeplug AV e IEEE 802.11n
POWERLINE 500M WIRELESS N EXTENDER TP-LINK TL-WPA4220KIT- INCL. TL-WPA4220 + 1 TL-PA4010 - GARANZIA 3 ANNI-
FINO:31/12

Valutazione: Nessuna valutazione

Prezzo

30,00 €

[Fai una domanda su questo prodotto](#)

Descrizione **NETWORKING WIRELESS:** TP-LINK

Modello: 1 TL-WPA4220 + 1 TL-PA4010

Velocità: 600 Mbps

Compatibilità: Homeplug AV e IEEE 802.11n

POWERLINE 500M WIRELESS N EXTENDER TP-LINK TL-WPA4220KIT- INCL. TL-WPA4220 + 1 TL-PA4010 - GARANZIA 3 ANNI-
FINO:31/12

Speed

Poweline 200Mbps

Wi-Fi 300Mbps

Standard&Protocol

HomePlugAV

IEEE 802.3,IEEE 802.3u

IEEE802.11 b/g/n

Interface

1*10/100M(Ethernet Interface)

Antenna

2*Internal antenna

Button

1*Pair

1*WPS/Reset

LED

1*Power

1*Powerline

1*Ethernet

1*Wi-Fi

1*WPS

Power Consumption

Maximum: 6.5W (220V/50Hz)

Standby:5.5W (220V/50Hz)

Power Input

AC 100~240V 50/60Hz 0.1A

Frequency

Powerline:2-30MHz

Wireless:2.4~2.4835GHz

Dimension

94mm*60mm*27mm

Certification

CE,FCC,RoHS

Plug Type

EU,UK,US

Package Content

AV200 Wi-Fi Powerline Extender

Quick Installation Guide

Ethernet Cable

Environment

Operating Temperature: 0°C ~ 40°C(32°F ~ 104°F)

Storage Temperature: -40°F ~ 158°F (-40°C ~ 70°C)

Operating Humidity:10% ~ 90% RH non-condensing

Storage Humidity:5% ~ 90%RH non-condensing.

Related Products

P200

Speed

Powerline 200Mbps

Standard&Protocol

HomePlugAV

IEEE 802.3,IEEE 802.11u

Interface

1*10/100M(Ethernet Interface)

Modulation Technology

OFDM,CSMA/CA

Button

1*Pair/Reset

LED

1*Power

1*Powerline

1*Ethernet

Power Consumption

Maximum: 2.8W (220V/50Hz)

Minimum: 0.43W (220V/50Hz)

Power Input

AC 100~240V 50/60Hz 0.1A

Frequency

Powerline:2-30MHz

Dimension

53mm*53mm*27mm

Certification

CE,FCC,RoHs

Plug Type

EU,UK,US

Package Content

AV200 Powerline Adapter

Quick Installation Guide

Ethernet Cable

Environment

Operating Temperature: 0°C ~ 40°C(32°F ~ 104°F)

Storage Temperature: -40°F ~ 158°F (-40°C ~ 70°C)

Operating Humidity:10% ~ 90% RH non-condensing

Storage Humidity:5% ~ 90%RH non-condensing.

Related Products

PW201A

Recensioni

Nessuna recensione disponibile per questo prodotto.